Amogh.ai

INTELLIGENT VIDEO RECORDER (IVR)

31B Series

Built for Video Intelligence at your business.



*based on software license

Operating: 10-35°C (50-95°F)

Supported Licenses

LIC-IVR-31B-CRE Core Amogh Al IVR - 16 streams, 30 days of storage, up to 2 MP, no Al features

LIC-IVR-31B-D30 Pro Amogh Al IVR - 16 streams, 30 days of storage

Supports 30 days of storage, up to 16 cameras, Core and Pro licenses.

System

Processor 10th generation Intel® Core™ i5-10400 Storage Capacity 30 days / 12 TB

processor (2.90 GHz, up to 4.30 GHz with Turbo Boost, 6 cores, 12 threads, recording 24/7 at 15fps)

12 MB cache) Recording Resolution 2MP/5MP*

OS M.2 drive 256 MB (Suggested)

SFF: 92.5mm x 309.7mm x 339.5mm

Al Accelerators Yes Video Output Display Port

Memory 2 x 8G DDR4 2933 Third-party camera Yes

Support

Camera Capacity Up to 16 streams*

*based on software license I/O Ports 2x RJ45 Gigabit Ethernet

Video decoding H.264/H.265 8x USB3
1x Display Port

Mechanical

Dimensions

format supported

Temperature Storage: -40-60°C (-40-140°F) **Weight** 12.6 lbs.

Environmental

Operating

Operating Humidity Operating: 20–80%

Power Supply 380W (92% efficient) Storage: 10–90%

Amogh.ai

INTELLIGENT VIDEO RECORDER (IVR)

31B Series

Built to bring the next level of Video Intelligence to your business.



Supported Licenses

Amogh Al IVR - 16 streams, 60 days of storage LIC-IVR-31B-D60 Pro Amogh Al IVR - 16 streams, 90 days of storage LIC-IVR-31B-D90 Pro

Supports 60/90 days of storage, up to 16 cameras, and Pro license.

System

OS M.2 drive

256 MB

Processor 10th generation Intel® Core™ i5-10400 60 days / 24 TB **Storage Capacity** 90 days / 36 TB

(16 camera streams processor (2.90 GHz, up to 4.30 GHz recording 24/7 at 15fps) with Turbo Boost, 6 cores, 12 threads,

12 MB cache) **Recording Resolution** 5MP (Suggested)

Video Output Display Port **Al Accelerators** Yes

Third-party camera Yes 2 x 8G DDR4 2933 Memory support

Camera Capacity Up to 16 streams* I/O Ports 2x RJ45 Gigabit Ethernet *based on software license

8x USB3 Video decoding H.264/H.265 1x Display Port format supported

Mechanical

Dimensions Tower: 170mm x 315.35mm x 376mm Operating Operating: 10-35°C (50-95°F) **Temperature** Storage: -40-60°C (-40-140°F)

Environmental

Weight 20.7lbs **Operating Humidity** Operating: 20–80%

Power Supply 500W (92% efficient) Storage: 10-90%